



SCHEMA DI MONTAGGIO - ASSEMBLY SCHEDULE

COD. **58.0807.00 / 58.0808.00**

REV. **00** DEL. **18/03/2019** TEC-LOG **G.D.**

Descrizione **Audi RS6(4G)**

Fig. 1 lato sinistro - left side - gauche - izquierda - linke seite






-  Togliere parte della pellicola per trovare le due filettature.
-  Remove part of the film to find the two threads
-  Enlevez une partie du film pour trouver les deux filetages
-  Retirar parte de la película para encontrar los dos hilos
-  Entfernen Sie einen Teil des Films, um die beiden Gewinde zu finden



Fig. 1



Fig. 2






-  Fissare la staffa in dotazione al montante della vettura ed agganciare lo scarico utilizzando il gommino!
-  Fix the brackets in equipment on the platform of the car and hook the exhaust by using the gum-ring;
-  Fixer l'étrier en dotation sous la coque de la voiture et en utilisant le petit bouchon en caoutchouc accrocher l'échappement!
-  Fijar el estribo en dotación al cuerpo del coche y enganchar el escape utilizando el anillo de goma!
-  Fixieren Sie die Schelle des Montagekits unter dem Karosseriekörper und setzen Sie die Anlage mit Hilfe des Gummiringes ein!



Fig. 2



Fig. 3 lato destro - right side - droite - derecho - Rechte seite






-  Togliere parte della pellicola per trovare le due filettature.
-  Remove part of the film to find the two threads
-  Enlevez une partie du film pour trouver les deux filetages
-  Retirar parte de la película para encontrar los dos hilos
-  Entfernen Sie einen Teil des Films, um die beiden Gewinde zu finden



Fig. 4






-  Fissare la staffa in dotazione al montante della vettura ed agganciare lo scarico utilizzando il gommino!
-  Fix the brackets in equipment on the platform of the car and hook the exhaust by using the gum-ring;
-  Fixer l'étrier en dotation sous la coque de la voiture et en utilisant le petit bouchon en caoutchouc accrocher l'échappement!
-  Fijar el estribo en dotación al cuerpo del coche y enganchar el escape utilizando el anillo de goma!
-  Fixieren Sie die Schelle des Montagekits unter dem Karosseriekörper



Fig. 4

